



AWWA C905-10 Municipal Water Pipe Certification

To Whom It May Concern:

Please be advised that the North American Pipe Corporation pipe products:

AWWA C905-10 PVC Water Distribution Pipe, Sizes 14"-36", DR41, DR32.5, DR25, DR21, and DR18

Provided by North American Pipe Corporation is manufactured in accordance with the following standards:

AWWA C905-10 Standard for Polyvinyl Chloride (PVC) Pressure Pipe and Fabricated Fittings, 14 In. Through 48 In. (350 mm Through 1,200 mm), For Water Transmission and Distribution

ASTM F477 Standard Specification for Elastomeric Seals (Gaskets) for Joining Plastic Pipe

ASTM D3139 Standard Specification for Joints for Plastic Pressure Pipes Using Flexible Elastomeric Seals

The PVC material conforms to a cell classification of 12454 as defined by ASTM D1784 *Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds*. The standard pipe laying length is 20 feet. The pipe is listed by Underwriters Laboratories, approved by Factory Mutual in 14" and 16" diameters only, and is listed by NSF International to ANSI/NSF 61.

Mike Glasgow, P.E.
Engineering and Field Services

Quality Piping Materials